


HOW TO REMOVE OLD AUDIO WIDGET DRIVERS ON WINDOWS 7


This text applies if you have installed an UAC2 ASIO driver from before 2013-02-11. If you have that version, or if you have no UAC2 ASIO driver installed, you may ignore this document.

You must follow these steps before installing the ASIO drivers and Widget-Control with the updated USB PID codes.


1. Unplug Audio-Widget / AB-1.2 from your computer
2. Uninstall Audio-Widget in Start menu or C:\Program Files (x86)\Audio-Widget



3. Open the Start menu and type in "cmd". On the icon on top, right-click and choose "Run as Administrator". Click "OK" in the User Account Control window.



4. At the command prompt, type in "set devmgr_show_nonpresent_devices=1" and press Enter. (Note that nothing seems to happen. This is expected. You are actually setting an environment variable which is going to help you to see hidden devices.) See next picture.
5. On the next command prompt line, type "devmgmt.msc" and press Enter. This will launch the Windows Device Manager Console.



6. In the Device Manager Console, from the View menu, select "Show Hidden Devices".






7. Search under tabs for

"libusbK USB Devices", "Sound, video...", "Audio-Widget...", "UAC2..."

Under all those tabs, delete and uninstall all drivers and anything resembling:

"Audio-Widget", "SDR-Widget", "DG8SAQ", "QNKTC", "Yoyodyne", "UAC2"



8. You should now be ready to install the new fresh version of the drivers!